

Ideen leben



Always a little more flexible:

hawa Accessories Sensor Operated LED-lamp





häwa Sensor Operated LED-Lamp

- Sensor controlled On/Off function
- Adjusted sensor
- Wide-range voltage
- Long service life, maintenance-free
- Energy-saving thanks to LED technology



Advice from one of our häwa consultants:

Use our service.
Luminaire attachment in series 33
wall-mount enclosures WITHOUT
refinishing operation such as
drilling. When enquiring, please
state the order number:
0302-7041-14-00



Here you can
find detailed
information to
this product.



Product Description

- The integrated Reflex light barrier (sensor) provides broad, homogeneous illumination as soon as the door is opened. The light goes out when the door is closed.
- Once the luminaire is mounted, the pre-adjusted sensor is operable.
- The LED luminaires are perfectly suitable for use in cabinets and enclosures with electric/electronic interior fittings and high packing density.
- These luminaires have a very long service life thanks to the use of LED technology.
- They are connected via plug-in connector with lock and integrated power supply unit.
- Luminaires can be wired in series (cascaded).

Scope of Delivery

- 1 piece

Notice

- Suitable for häwa free-standing cabinets of the H370, H375, H390, H395 series as well as häwa 600, 800, 1000 and 1200 mm cabinets and cabinets from other manufacturers with 25 mm grid perforation.
- Suitable for häwa wall-mount enclosures, series 33, with width and height exceeding 500 mm.
- We recommend fastening the luminaire after mounting all interior fittings (e.g. mounting plate).

Technical Data

- Design: Sheet steel enclosure, powder-coated RAL 7024, texture finish
- Luminous flux: 1,200 lm at 120°
- Switch: Reflex light barrier
- Power consumption: max. 10 W
- Light source: LED, beam angle 120°
- Color temperature: 5,000 K
- Connection: 3-pin plug-in connector with lock
- In-series mounting: max. 10 units
- Operating temperature range: -15 °C to +45 °C
- Storage temperature range: -25 °C to +60 °C
- Degree of protection: IP20
- Weight: 0.8 kg
- Mounting type: Screw fastening M5
- Dimensions: 440 x 65 x 42 mm (L x W x H)
- Service life: 60,000 h at +20 °C (+68 °F)
- Approvals: CE, VDE-EMV

Accessories








- AC/DC Power cable, length: 3,000 mm:
3080-9042-25-73 (AC), 3080-9042-25-24 (DC)
- AC/DC connection cable, length: 700 mm:
3080-9042-05-73 (AC), 3080-9042-05-24 (DC)
- AC/DC connection cable, length 1,200 mm:
3080-9042-10-73 (AC), 3080-9042-10-24 (DC)

Version	Operating voltage	Order number
with shockproof socket 16A	AC 100-240V, 50/60 Hz (min. AC 90V, max. AC 264V)	3080-7041-14-17
without shockproof socket	AC 100-240V, 50/60 Hz (min. AC 90V, max. AC 264V)	3080-7041-14-07
without shockproof socket	DC 24V ± 10% at 120Vpp ripple	3080-7041-24-07

häwa GmbH
 Industriestraße 12
 D 88489 Wain
 Tel. +49 7353 98460
 Fax +49 7353 1050
 info@haewa.de
 www.haewa.de



<p>D 08451 Crimmitschau Sachsenweg 3 Tel. +49 3762 95271/2 Fax +49 3762 95278 vertrieb.c@haewa.de</p>	<p>D 47167 Duisburg Gewerbegebiet Neumühl Theodor-Heuss-Str. 128 Tel. +49 203 346530 Fax +49 203 589785 vertrieb.d@haewa.de</p>	<p>D 63477 Maintal Dörnigheim Carl-Zeiss-Straße 7 Tel. +49 6181 493031 Fax +49 6181 494003 vertrieb.rm@haewa.de</p>	<p>A 4020 Linz Schmachtl GmbH Pummererstraße 36 Tel. +43 732 76460 Fax: +43 732 785036 office.linz@schmachtl.at</p>
<p>CH 8967 Widen häwa (Schweiz) ag Gyrenstrasse 5a Tel. +41 43 3662222 Fax +41 43 3662233 info@haewa.ch</p>	<p>DK 6400 Sonderborg Eegholm A/S Grundtvigs Allé 165 - 169 Tel. +45 73 121212 Fax: +4573 121213 eegholm@eegholm.dk</p>	<p>E 48450 Etxebarri hawea ibérica, s.l. Poligono Leguizamón Calle Guipuzcoa, Pab.9 Tel. +34 944 269521 Fax: +34 944 261087 hawea@ctv.es</p>	<p>F 67140 Eichhoffen häwa France Sarl 8 B Rue des Industries Tel. +33 3 88088880 Fax: +33 3 88088859 info@haewa.fr</p>
<p>I 88489 Wain häwa Italia Industriestraße 12 Tel. +49 7353 9846115 Fax +49 7353 1050 info@haewa.it</p>	<p>NL 7500 AC Enschede häwa Nederland B.V. Postbus 136 Tel. +31 53 4321835 Fax +31 53 4303414 info@haewa.nl</p>	<p>SE 88489 Wain häwa Schweden Industriestraße 12 Tel. +49 7353 98460 Fax +49 7353 1050 info@haewa.se</p>	<p>SE 192 79 Sollentua (only for tools) Nelco Contact AB Bergkällawägen 29 Tel. + 46 8 7547040 Fax +46 8 7548051 info@nelco.se</p>
<p>USA Duluth, GA 30097 haewa Corporation 3768 Peachtree Crest Drive Tel. +1 770 9213272 Fax +1 770 9212896 info@haewa.com</p>	<p>RUS 88489 Wain häwa Russland Industriestraße 12 Tel. +49 7353 9846 169 Fax +49 7353 1050 edgar.getz@haewa.de</p>		

	CABINET SYSTEMS
	X-FRAME
	ENCLOSURES
	ACCESSORIES
	CLIMATE CONTROL
	CABLE DUCTS
	CUSTOMIZED SOLUTIONS
	TOOLS