

Control Housings

for pendant arm systems

- **Strong & robust**
- **Excellent value**
- **In Stock**

**2 solutions designed for
HLT Pendant Arm System**

Steel Housings



Modified häwa wallmount 3331

- Hinged door on rear side
- Stiffening bracket with HLT cut-out integrated in top
- Handle bars on front sides (RAL 7016 – anthracite gray)
- UL Type 12

Aluminum Housings



' TOUCH '



' BASIC '

Built from extruded aluminum

- Configurations:
 - ' BASIC '
 - ' TOUCH ': with handle bars
 - ' COOL ': with heat sink on sides
- Many variations available



' COOL '



Housings can be used hanging or standing on the arm system!

Re-inforced roof to connect to HLT joints & adapters

US-Stocked Sizes!

hawa control housings
designed for HLT pendant arm system

DON'T FIND THE CONFIGURATION YOU NEED?
PLEASE CONTACT HAEWA FOR ANY MODIFICATION
OR CUSTOMIZATION AT 1-800-783-4239

	Size [inches] H x W x D (nominal)	Size [mm] H x W x D (exact)	Max. usable space on front side * H x W [mm]	Order No.	Weight lbs / kg
Steel Control Housings	14 x 14 x 4	350 x 350 x 100	350 x 300	USA7525-3535-10-07	14.3 / 6.5
	16 x 16 x 6	400 x 400 x 150	400 x 350	USA7525-4040-15-07	20.5 / 9.3
	20 x 20 x 8	500 x 500 x 200	500 x 450	USA7525-5050-20-07	31.1 / 14.1
	24 x 24 x 8	600 x 600 x 200	600 x 550	USA7525-6060-20-07	40.6 / 18.5
Aluminum Control Housings	14 x 14 x 3	350 x 350 x 90	290 x 290	7505-3535-09-12	11 / 5
	20 x 20 x 5	500 x 500 x 130	440 x 440	7505-5050-13-22	19 / 8.6

' BASIC '
' TOUCH '

* Please account for maximum space requirements of your equipment. Most equipment requires more space than just the cut-out dimensions!

Technical Data Steel Housings:

Material:

- Housing: Steel, powder-coated RAL 7035, structured
- Handle bars: Steel, powder-coated RAL 7016 structured

Protection Class

- IP 66 / UL Type 12

Rear Door

- Can be hinged on both sides
- Seamless, poured gasket
- Metal hinges, 180° opening angle
- Equipped with two perforated rails to mount additional equipment

Roof

- Reinforced and with cut-out to connect to HLT pendant arm system



Technical Data Aluminum Housings:

Material:

- Housing: Light weight aluminum/magnesium alloy
- Front plate: Aluminum, anodized
- Corner profiles: Aluminum, painted RAL 7016

Protection Class

- IP 54 / UL Type 1

Rear Door

- Many different configurations possible (please see catalog)
- Stocked product has a hinged backplate

Roof

- Reinforced and with cut-out to connect to HLT pendant arm system



' BASIC '



Hinged Backplate

Note: Additionally, any of our 3331-Series wallmount enclosures can be modified to be used as a control housing. A support bracket for the roof cut-out is available.
Attention: No corner profiles in this case! Consult with customer service for details.